

## Chevron Conveyor Belts

Chevron conveyor belts with a smooth carrying surface are useful for conveying of packed and unpacked Materials up to the angle of inclination 22° as an upper limit. Chevron belts are the right belts to meet your requirement when higher-quality chevron and high-chevron conveyor belts. there advantages are long service life and flexibility due to homogeneous chevron profile which are vulcanized together with a base belt.

### Area of applications

Quarries , sandpits  
Cement works, lime works  
Framing conveying of beets , grain, potatoes, fertilizers, wooden chips  
Coal and coke transport  
Sugar refineries  
Salt mines  
Mobile crushers and screens

### Features

- Longer working life
- Can carry loose materials at angle of 17-18 and bagged material at 30-35
- Cleat angle and pitch are designed for smooth travel over return idlers
- Cleats and the top cover rubber are mono block molding for strength

### Standard length

150 meters as per roll

### Standard width

500 mm to 1400 mm

### Grades

General purpose, flame resistance, oil resistance and heat resistance etc.

### Standard follow

National and international standards (IS, AS, BIS,DIN ETC.)



Clean type	belt width (mm)	Cleat width (mm)	Cleat hight (mm)	Cleat thickness (mm)	pitch (MM)
CK -A	400	full belt width	6	12	100
	450				
	500				
	600				
CK -a1	600	385	15	20	250
	650				
	700				
CK-a2	600	450	15	20	250
	650				
	700				
	750				
CK-a3	800	750	15	20	250
	900				
	1000				
	1050				
CK-a4	1200	575	15	20	330
	600				
	650				
	700				
	750				
CK-a5	800	450	25	25	250
	900				
	600				
	650				
	700				
CK-a6	750	550	25	25	250
	800				
	900				
	600				
CK-a7	650	750	25	25	330
	700				
	800				
	900				
CK-a8	1000	600	32	22	330
	900				
	1050				
	1200				
CK-9	800	620	17	20	375
	900				
	1000				
	1200				

