

## Sandwich Rubber Sheet

Sandwich is multi-layer rubber sheet especially designed for mining industry. Its top and bottom layer are high abrasion and cut resistance for handling mining materials and its inner layer is to give support to handle mining material smoothly.

### Features:

Superior resistant to dry abrasion and high impact. Excellent cut and gouge properties when sharp, heavy coarse particles present. Unique two colour abrasion resistant compounds enables handling mining material and inner layer support to mining material.

### Applications :

Lining of chutes, vessels, transfer points, vibratory feeders, impact chutes, distribution bins and sumps when critical wear monitoring is required.

### Finish Type :

Both side smooth finish.

**Standard Thickness :** 1 mm to 40 mm

**Standard Length :** 10 Metre, 33 Ft, 11 Yard

**Standard Width :** 1.2/1.4/1.5 Metre, 48"/54"/60 " inches

COLOR



## Technical Data Sheet

Code	Specific Gravity	Hardness	Tensile Strength	Elongation	Abrasion	Temperature
	Gm/cm <sup>3</sup>	(+/-5)	Kg/cm <sup>2</sup>	%	mm <sup>3</sup>	°C
	ASTM D297	Shore A	ASTM D412	ASTM D412	ASTM D5963	—
CK SW 60 150	1.15	60-40-60	150	500	100	-25 to +70
CK SW 75 120	1.25	75-45-75	120	350	200	-25 to +70